



5x3 Multi-Format Presentation Switcher & Recorder



Data Transfer Rate:
up to **18Gbps**


Part# CE-H26S11-S1

Easily switch and record to 4K display between HDMI/DP/USB-C devices and HDBastT-Lite technology to make your presentation more efficiency

Front view



Rear view



- Compliant with HDMI 2.0, HDCP 2.2/1.4 with 18Gbps video bandwidth
- Splits 3x HDMI 2.0/1x DP 1.2/1x USB-C input signals to 2x HDMI and 1x RJ45 with HDBaseT-Lite outputs
*** Note: HDMI receiver is an option and sold separately**
- Supports deep color, vxYCC and x.v.Color. HDMI video resolution up to 4K@60Hz (YUV 4:4:4 8-bit). 4K@30Hz (YUV 4:4:4 8-bit) and HDR 4K@60Hz (YUV 4:2:0 8-bit) via HDMI HDBaseT-Lite technology transmission
*** Note: Please turn off the 24Hz setting for playing Blue-rays with Xbox and this 5x3 Multi-Format Presentaion Switcher & Recorder doesn't support 4K@60Hz 4:2:2 10-bit**
- Extends HDMI signal by HDBaseT-Lite technology up to 70m (230ft) from the HDMI/DP/USB-C input sources Full HD 1080p 36-bit or 40m (133ft) 4K@60Hz (YUV 4:2:0 8-bit) and 4K@30Hz (YUV 4:4:4 8-bit)
- Supports 1080p video and voice recorders and recorder slide switch from USB 2.0 port or SD memory card slot; built-in / external 3.5mm microphone
- Easily switch audio sources by using the select buttons and supports firmware updated features

Common Applications

- Conference room, Presentation room, Lecture hall, Church, Exhibition, Home entertainment

