

DisplayPort to 2-Port HDMI Quick Installation Guide

Introduction

The *DisplayPort to 2-Port HDMI* distributes one DisplayPort source to two HDMI displays. Video wall array function is available while two *DisplayPort to 2-Port HDMI* splitters are used simultaneously.

Key Features and Benefits

- Distributes content from one DisplayPort to two HDMI outputs
- Works as a splitter with the same content on each display or expand mode, joining multiple screens together as one display
- Supports max resolution of 3840x1200 when connected to two displays
- Supports video wall function: Tiling multiple screens together to form one large screen
- Supports panoramic view

Package Contents

- DisplayPort to 2-Port HDMI
- Power adapter
- Housing rubber pad (4)
- Quick installation guide

Layout



Figure 1: Rear Panel Layout

- **DC 5V:** Power adapter jack for the included 5V power adapter
- **DP IN**: DisplayPort input. Connects to your DisplayPort source
- **Power LED:** Power LED indicator. On when power adapter is connected



Figure 2: Front Panel Layout

• HDMI (1-2): HDMI signal output. Connects to your HDMI displays

Hardware Installation

- 1. Power off all devices you plan to connect to this splitter.
- 2. Connect your source's DisplayPort out to the splitter's **DP** input using a DisplayPort cable (not included).
- 3. Connect your monitors to the splitter's **HDMI** output with HDMI cables (not included).
- 4. Connect the included power adapter to the splitter's power jack and plug it into a reliable power outlet.
- 5. Power on all of the connected devices.
- 6. The device is ready for use.

Application

The *DisplayPort to 2-Port HDMI* supports either 2 HDMI displays or 4 HDMI displays at the same time. However, mirror mode and extended mode are supported by 2 HDMI displays only.

2 HDMI output displays

Extended Mode




Figure 3

Mirror Mode Resolutions under 1920x1080:

2 HDMI output displays




Figure 4

Resolutions above 1920x1080:





Figure 5

4 HDMI output displays

Two *DisplayPort to 2-Port HDMI* splitters can work together as a 4-display video wall.





Graphic Card Setup

At the AMD Catalyst Control Center, click **AMD Eyefinity Muliti-Display** for advanced display mode setup. See **Figure 7**.

Refer to your graphic card menu for more details.

	Catalyst C	ontrol Center				
AMDA			Preferences			
Search 🔎 «	Create Eyefinity Display Group 🐐 ?					
> Pinned 🦸	Create an AM	Create an AMD Eyefinity display group. Combine multiple displays to work together as a single desktop.				
> Presets 🥩						
HydraVision™		Select the desktop for which you want to start creating an AMD Eyefinity display group.				
> Desktop Management	Eyefinity o	isplay group.				
Common Display						
 AMD Eyefinity™ Multi-Display 						
Create Eyefinity Display Group	*①	-	3			
> My Digital Flat- Panels	U	(2)	•			
> My VGA Displays 🛛 🚳						
> Video 🥁						
> Gaming р						
> Performance						
> Audio						
> Information						
			Digcard Apply			

Figure 7

Supported Video Resolutions

Refer to Table 1 for the supported resolution under different conditions (2 HDMI displays, or 4 HDMI displays via two *DisplayPort to 2-Port HDMI* splitters):

	Supported Video R	esolutions (TV Wall)		
Two Mo	onitors	Four Monitors (2x2)		
Computer Setting	Each Monitor	Computer Setting	Each Monitor	
3840 x 1200	1920 x 1200	3840 x 2400	1920 x 1200	
2560 x 1024	1280 x 1024	2560 x 2048	1280 x 1024	
2048 x 768	1024 x 768	2048 x 1536	1024 x 768	
3360 x 1050	1680 x 1050	3360 x 2100*	1680 x 1050	
2880 x 900	1440 x 900	2880 x 1800*	1440 x 900	
1600 x 600	800 x 600	1600 x 1200*	800 x 600	
1280 x 480	640 x 480	1280 x 960*	640 x 480	
2800 x 1050	1400 x 1050	2800 x 2100*	1400 x 1050	

Table 1

***Note:** The timing is listed in EDID extension block. Some old display drivers may not support it.

The actual output resolution is determined by the EDID of each display. We suggest that you use the same brand and model displays for the best video output.

Blank Page

Blank Page

Technical Support and Warranty

QUESTIONS? SIIG's Online Support has answers! Simply visit our web site at www.siig.com and click Support. Our online support database is updated daily with new drivers and solutions. Answers to your questions could be just a few clicks away. You can also submit questions online and a technical support analyst will promptly respond.

SIIG offers a 3-year manufacturer warranty with this product. This warranty covers the original purchaser and guarantees the product to be free of any defects in materials or workmanship for three (3) years from the date of purchase of the product.

SIIG will, at our discretion, repair or replace (with an identical product or product having similar features and functionality) the product if defective in materials or workmanship. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Please see our web site for more warranty details.

If you encounter any problems with this product, please follow the procedures below.

A) If it is within the store's return policy period, please return the product to the store where you purchased from.

B) If your purchase has passed the store's return policy period, please follow the steps below to have the product repaired or replaced.

Step 1: Submit your RMA request.

Go to www.siig.com, click Support, then REQUESTA PRODUCT REPLACEMENT to submit a request to <u>SIIG RMA</u> or fax a request to 510-657-5962. Your RMA request will be processed, if the product is determined to be defective, an RMA number will be issued.

Step 2: After obtaining an RMA number, ship the product.

- Properly pack the product for shipping. All accessories that came with the original package must be included.
- Clearly write your RMA number on the top of the returned package. SIIG will
 refuse to accept any shipping package, and will not be responsible for a product
 returned without an RMA number posted on the outside of the shipping
 carton.
- You are responsible for the cost of shipping to SIIG. Ship the product to the following address:

```
SIIG, Inc.
6078 Stewart Avenue
Fremont, CA 94538-3152, USA
RMA #:
```

 SIIG will ship the repaired or replaced product via Ground in the U.S. and International Economy outside of the U.S. at no cost to the customer.

About SIIG, Inc.

Founded in 1985, SIIG, Inc. is a leading manufacturer of IT connectivity solutions (including Serial ATA and Ultra ATA Controllers, FireWire, USB, and legacy I/O adapters) that bridge the connection between Desktop/Notebook systems and external peripherals. SIIG continues to grow by adding A/V and Digital Signage connectivity solutions to our extensive portfolio. SIIG products offer comprehensive user manuals, many user-friendly features, and are backed by an extensive manufacturer warranty. High quality control standards are evident by the overall ease of installation and compatibility of our products, as well as one of the lowest defective return rates in the industry. SIIG products can be found in computer retail stores, mail order catalogs, through major distributors, system integrators, and VARs in the Americas and the UK, and through e-commerce sites.

PRODUCT NAME

DisplayPort to 2-Port HDMI

FCC RULES: TESTED TO COMPLY WITH FCC PART 15, CLASS B OPERATING ENVIRONMENT: FOR HOME OR OFFICE USE

FCC COMPLIANCE STATEMENT:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

THE PARTY RESPONSIBLE FOR PRODUCT COMPLIANCE SIIG, Inc. 6078 Stewart Avenue Fremont, CA 94538-3152, USA Phone: 510-657-8688

DisplayPort to 2-Port HDMI is a trademark of SIIG, Inc. SIIG and the SIIG logo are registered trademarks of SIIG, Inc. All other names used in this publication are for identification only and may be trademarks of their respective owners.

February, 2013

Copyright © 2013 by SIIG, Inc. All rights reserved.