

DVI Splitter Single Link EDID

Timing characteristics

Horizontal scan range...30-83 kHz

Vertical scan range..... 56-76 Hz

Video bandwidth..... 160 MHz

CVT / GTF standard.....Not supported

Additional descriptors... None

Preferred timing.....Yes

Native/preferred timing: 1920x1200p at 60Hz (16:9)

Standard timings supported

720 x 400p	70Hz	IBM VGA
640 x 480p	60Hz / 75Hz	IBM VGA / VESA
800 x 600p	60Hz / 75Hz	VESA
1024 x 768p	60Hz / 75Hz	VESA
1152 x 864p	75Hz	VESA STD
1280 x 1024p	60Hz	VESA STD
1680 x 1050p	60Hz	VESA STD
1920 x 1080p	60Hz	VESA STD
1920 x 1200p	60Hz	VESA STD

DVI Splitter Dual Link EDID

Timing characteristics

Horizontal scan range...24-140 kHz

Vertical scan range..... 50-122Hz

Video bandwidth..... 290 MHz

CVT / GTF standard.....Not supported

Additional descriptors... None

Preferred timing..... ...Yes

Native/preferred timing: 2560x1600p at 60Hz (16:9)

Standard timings supported

720 x 400p	70Hz	IBM VGA
640 x 480p	60Hz / 75Hz	IBM VGA / VESA
800 x 600p	56Hz / 60Hz / 72Hz / 75Hz	VESA
1024 x 768p	60Hz / 70Hz / 75Hz	VESA
1280 x 720p	60Hz	VESA STD
1280 x 960p	60Hz	VESA STD
1280 x 1024p	60Hz / 75Hz	VESA STD
1440 x 900p	60Hz	VESA STD
1680 x 1050p	60Hz	VESA STD
1920 x 1200p	60Hz	VESA STD
2048 x 1152p	60Hz	VESA STD
2560 x 1600p	60Hz	VESA STD