

User Reference Guide

Compact and easy to bring on the road

Thanks for purchasing SIIG product. Please read this manual carefully prior to use.

If you require more information about our products, please visit www.siig.com.

For technical support, please go to www.siig.com/support.

Product Layout



Package Contents

Mini DisplayPort 1.2 to HDMI / DVI / VGA Conversion Adapter

User Reference Guide

Specifications

- Input: Mini DisplayPort 1.2 (Dual-mode) / Thunderbolt Port Male
- Output: HDMI Female / DVI Female / VGA Female
- Max resolution:
 HDMI: 4K x 2K (w/ audio)
 - -DVI & VGA: 1920 x 1080 @ 60HZ (w/o audio)
 - -DVI & VGA: 1920 x 1080 @ 60HZ (w/o audio
- Power: Supplied by Mini DisplayPort (No external power required)
- Connector type of Mini DisplayPort: Golden-plated

Start using

Connections

 $\label{lem:minimizer} \begin{tabular}{ll} Mini DisplayPort: Connect to the Mini DisplayPort of the competer $HDMI/DVI/VGA Port: Choose one port to connect with your monitor / HDTV / Projecter by individual monitor cable (not included) $$$

- Notes
- $1. \ \ The adapter does {\color{red} not} support {\color{red} more} {\color{red} than} {\color{gray} one} {\color{gray} output} simultaneously.$
- The adapter supports converting signal from Mini DisplayPort to HDMI /DVI / VGA only. It's not a bi-directional adapter.
- 3. There's no audio output from DVI and VGA.
- Macs manufactured before 2010 do not support audio output over Mini DisplayPort.

 To achieve Mini DisplayPort 1.2 performace, please make sure that the connected input source is also Mini DisplayPort 1.2 supported.

FAO & Solutions

If I would like to switch to another output of the adapter, how should I do?

 Unplug the connected monitor cable from the adapter, then plug another monitor cable into the output port you are going to use.

If the adapter isn't working properly:

- Check all connections of the adapter and monitor cable are firm.
 - Unplug the connected monitor cable from the adapter and plug again.
- If above doesn't work, unplug the adpater from the Mini DisplayPort of the computer and plug again.

If the max. resolution of HDMI output couldn't reach 4K x 2K:

 $\bullet \quad \text{Check that whether the connected monitor is } 4K\,x\,2K\,\text{supported}.$



3 years warranty limited Mon-Fri 8:00~17:00 (510) 657-8688 www.siig.com





